

Isolation Transformer & Ultra Isolation Transformer

Salient Features

- ◆ Isolates the equipment from noisy power line
- ◆ Reduces power line Noise, Surges, Spikes & Transients.
- ◆ High Insulation resistance
- ◆ Provides the complete Electromagnetic & Electro static shielding.

Applications

Computers & Peripherals, Analytical Instruments, Communication Equipments, CNC Machines, Medical Instruments, Testing & Measuring Equipments....



Isolation Transformer Specifications

Input Voltage	: 220 Volts
Output Voltage	: 220 Volts
Transformer Ratio	: 1:1
Power Factor	: 0.75 Lag to lead
Frequency	: 50 Hz
VI Electric strength	: 2500 V AC for 120 sec.
Insulation resistance	: More Than 100M Ohms.
Capacitance Coupling	: 0.01 PF 100 db
Common Mode attenuation	: 100 db
Class Of Insulation	: Class 'F'
Losses	: 5%
Ambient temperature	: 0-50o C
Duty Cycle	: Continuous
Lamination	: Cargo
Construction	: as per IS :2026

Ultra Isolation Transformer Specifications

Phase	: Three Phase
Input voltage	: 415 Volts
Output Voltage	: 415 Volts
Systems Construction	: Delta / Star
Transformer Ratio	: 1:1
Regulation	: Better Than 4%
Power Factor	: 0.75 Log to lead
Frequency	: 50 Hz
VI Electric strength	: 2500 V AC for 120 sec.
Insulation Resistance	: More Than 1000M Ohms.
Capacitance Coupling	: 0.01 PF 100 b.b
Common Mode attenuation	: 100 b.b
Class Of Insulation	: Class 'F'

A Product From :

VAIBHAVA HITECH SYSTEMS

C4 - 88, Safdarjung Development Area, Opposite I.I.T. Main Gate, New Delhi – 110 016.

Ph: ++91 – 11- 2685 9248, 2686 6011. Fax: ++91 - 11 - 2685 9248

Mobile: **98 112288 36, 98 11299 611, 99 1122 7838, 99 1122 7836**

E-mail: vhs999@gmail.com / vhs99@rediffmail.com / info@arieselectric.net

www.arieselectric.net